

CE

0120

O'Reilly Concrete, Larchfield, Kingscourt Co. Cavan Ireland

13

GB13/89585

EN 1168

Hollow core slabs for floors

PRESTRESSED HOLLOW CORE SLAB (for floors)

Concrete:

Compressive strength $f_{ck} = 50 \text{ N/mm}^2$

Reinforcing steel:

Prestressing steel:

Ultimate tensile strength $f_{pk} = 1770 \text{ N/mm}^2$ Tensile 0,1% proof-stress $f_{p0,1k} = 1557 \text{ N/mm}^2$

For geometrical data, detailing, mechanical strength, fire resistance, acoustic insulation parameters and durability see the design specifications

Design Specification: Precast Structures Design

Specification

Order Code: To Clients order



DECLARATION OF PERFORMANCE		
Trade Name:	O'Reilly Concrete	
Place of Manufacture:	Larchfield, Kingscourt, Co. Cavan	
Product Type:	PRESTRESSED HOLLOW CORE SLAB (for floors)	
Unique Identification Code:	HC - 150	
Intended Use:	Flooring and roofing for single and multi storey developments	
System of Assessment:	System 2+	
Notified Certification Body:	SGS UK Ltd	
	Unit 202b Worle Parkway	
	Weston-super-Mare	
	Somerset BS22 6WA	
Notified Body Number:	0120	
DECLARED PERFORMANCE:		
Essential Characteristics	Performance	Harmonised Technical Standard
Compressive Strength	50N/mm ²	
Reinforcing Steel:		
Ultimate tensile strength, f_{tk}	500N/mm ²	
Tensile yield strength, f _{yk}	600N/mm ²	
Prestressing Steel:		
Ultimate tensile strength, f_{pk}	1770N/mm ²	EN 1168:2005
Tensile 0.1% proof-stress, $f_{p0.1k}$	1557N/mm ²	
Mechanical Strength (by calculation)	Refer to Design Specification	
Resistance to fire (for load bearing	Refer to Design Specification	
capacity)		
Airbourne sound insulation and	NPD	
impact noise transmission		
Detailing	Refer to Detailed Drawings and	
	technical documentation	
Durability	Refer to Design Specification	
Signed on Behalf of Manufacturer	Bany o Reelly	FULL NAME: Barry O'Reilly
Position	Managing Director	20 August 2013